

PRODUCT SPECIFICATIONS SHEET

Model: Jazzy 600 Series

Manufacturer: Pride Mobility Products Corp.

Internet Address: www.pridemobility.com

Document Information: INFNFB2754/Rev 50A/August 2011

* I N F I N F B 2 7 5 4 *

Suspension:	ATX Suspension (Active-Trac with extra stability)
Drive Wheels:	Jazzy 600: 14 in. (35.56 cm), pneumatic or solid available Jazzy 600 XL: 14 in. (35.56 cm), solid
Caster Wheels:	Front: 5 in. (12.7 cm) solid Rear: 6 in. (15.24 cm) solid
Maximum Speed: ¹	Jazzy 600: Up to 5 mph (8 km/h) Jazzy 600XL: Up to 4 mph (6.43 km/h)
Range: ^{1, 4}	Jazzy 600: Variable up to 15.5 miles (25 km) Jazzy 600 XL: Variable up to 15 miles (24.1 km)
Brakes:	"Intelligent Braking" electronic regenerative, disc park brake
Ground Clearance: ²	1.375 in. (3.5 cm) at rear skidbar 3 in. (7.62 cm) under main frame
Maximum Allowable Incline:	8° (14.1%)
Turning Radius: ²	20 in. (50.8 cm)
Overall Size: ^{2, 6}	Jazzy 600 Length: 40.5 in. (102.87 cm) with front riggings Jazzy 600 Length: 36.5 in. (90.17 cm) without front riggings Jazzy 600 XL Length: 41.5 in. (105.41 cm) with front riggings Jazzy 600 XL Length: 37.5 in. (95.25 cm) without front riggings Jazzy 600 and Jazzy 600 XL Width: 23 in. (58.42 cm)
Drivetrain:	Two motor, mid-wheel drive
Batteries: ³	Two 12-volt, deep cycle NF-22 batteries
Battery Charger:	5-amp, off-board
Weight Capacity:	Jazzy 600: 300 lbs. (136 kg) Jazzy 600XL: 450lbs. (181 kg)
Maximum Angle Capacity	10° (17.6%)
Maximum Obstacle Climbing Ability	2.95 in. (7.5 cm)
Component Weights: ⁵	Base: 127 lbs. (50.6 kg) Standard Seat (with controller): 44 lbs. (19.95 kg) Batteries: 35 lbs. (15.87 kg) each

¹ Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM or Gel-Cell type required. See VI. "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 Series EN12184 standards. All specifications subject to change without notice.

