

PRODUCT SPECIFICATIONS SHEET

Model: 336

Document Information: INFINF B4218/Rev A/March 2020

Model Number	336
Weight Capacity	275 lbs. (125 kg)
Maximum Speed ¹	Up to 4.25 mph (6.8 km/h)
Ground Clearance ²	2.5 in. (64 mm) at mid-frame
Turning Radius ²	32.5 in. (826 mm)
Overall Length ²	37 in. (940 mm)
Overall Width ^{2,7}	19.5 in. (495 mm)
Tires	8 in. (203 mm), solid
Range Per Charge ^{1,4}	Up to 6.11 miles (9.8 km) with 12 Ah batteries
Total Weight Without Batteries ⁵	73.5 lbs. (32.5 kg)
Heaviest Piece When Disassembled (Front Section)	25.5 lbs. (11.5 kg)
Standard Seating	Type: Foldable Material: Black Vinyl Width: 17 in. (432 mm) Depth: 17 in. (432 mm) Weight: 23.5 lbs. (10.75 kg)
Drive System	Rear-wheel drive, sealed transaxle, 24 volt DC motor
Dual Braking System	Regenerative and electromechanical
Battery Requirements ^{3,6}	Type: Two 12-volt, deep-cycle Size: 12 Ah Weight: 9 lbs. (4 kg) each
Battery Pack Weight	18.5 lbs. (8.5 kg)
Battery Charger	Off-board charger
Freewheel Operational Force	Less than 60 N
Drive Control Operational Force	Less than 5 N
Maximum Rated Slope	6° (10.5%)
Measured Sound Level (A-weighted)	Less than 65 dB

¹ Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tire type and tire condition. This specification can be subject to a variance of + 10% -5%.

² Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM, Gel-Cell or Hybrid Gel (hybrid gel is defined as a nano silica gel electrolyte with high quality glass mat separators) required. See III. "Batteries and charge."

⁴ Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Includes standard seat

⁶ Battery weight may vary based on manufacturer.

⁷ Overall scooter width at seat is 22.3 in. (56.64 cm)

NOTE: This product conforms to all applicable ANSI-RESNA testing requirements and ISO 7176 series standards. All specifications subject to change without notice.



