

PRODUCT SPECIFICATIONS SHEET

Model: Travel Pro (SC36)

Manufacturer: Pride Mobility Products Corp.

Internet Address: www.pridemobility.com

Document Information: INFINF2486/Rev B/January 2011

Model Number	SC36
Maximum Safe Slope	8° (14.1%)
Maximum Climbing Ability	8° (14.1%)
Maximum Obstacle Climbing Ability	2 in. (5 cm)
Overall Length²	37 in. (93.98 cm)
Overall Width^{2,7}	19.5 in. (49.53 cm)
Total Weight Without Batteries⁵	73.5 lbs. (32.65 kg)
Heaviest Piece When Disassembled (Front Section)	25.5 lbs. (11.6 kg)
Turning Radius²	32.5 in. (82.55 cm)
Speed (maximum)¹	Variable up to 4.25 mph (6.83 km/h)
Range Per Charge^{1,4}	Up to 6.11 miles (9.83 km) with 12 Ah batteries
Ground Clearance²	2.5 in. (6.35 cm) at mid-frame
Weight Capacity	275 lbs. (125 kg)
Standard Seating	Type: Foldable Material: Black Vinyl Width: 17 in. (43.18 cm) Depth: 17 in. (43.18 cm) Weight: 23.5 lbs. (10.7 kg)
Drive System	Rear-wheel drive, sealed transaxle, 24 volt DC motor
Dual Braking System	Regenerative and electromechanical
Tires	8 in. (20.32 cm) solid
Battery Requirements^{3,6}	Type: Two 12-volt, deep-cycle Size: 12 Ah Weight: 9 lbs. (4.08 kg) each
Battery Pack Weight	18.5 lbs. (8.4 kg)
Battery Charger	Off-board charger

¹ Varies with user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, tire type and tire condition. This specification can be subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM or Gel-Cell type required. See IV. "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculation based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Includes standard seat

⁶ Battery weight may vary based on manufacturer.

⁷ Overall scooter width at seat is 22.3 in. (56.64 cm)

NOTE: This product conforms to all applicable ANSI-RESNA testing requirements and ISO 7176 series EN12184 standards. All specifications subject to change without notice.

